

Safety Data Sheet

according to Regulation (EU) No. 1907/2006

140.000 Renia - Ortec - Contactadhesive

Print date : 14.08.2007

Product code : 132

Page 2 of 7

Take off all contaminated clothing immediately. Wash off with soap and water. Grease skin after contact.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult a physician.

After ingestion

Do not induce vomiting. Call a physician immediately.

Advice to doctor

In case of shortness of breath, give oxygen. Risk of product entering the lungs on vomiting after ingestion.

5. Fire-fighting measures

Suitable extinguishing media

Suitable extinguishing media carbon dioxide (CO₂) dry chemical foam

Extinguishing media which must not be used for safety reasons

high volume water jet

Special exposure hazards arriving from substance or preparation itself, combustion products, resulting gases

In the event of fire and/or explosion do not breathe fumes. In use, may form flammable/explosive vapour-air mixture.

Special protective equipment for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Additional information

Use water spray to cool unopened containers.

6. Accidental release measures

Personal precautions

Remove all sources of ignition. When using do not smoke.

Environmental precautions

Do not let product enter drains.

Methods for cleaning up/taking up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Dispose of as special waste in compliance with local and national regulations

7. Handling and storage

Handling

Advice on safe handling

Use only in well-ventilated areas. Keep container tightly closed. Keep away from heat.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. In use, may form flammable/explosive vapour-air mixture. Cool containers / tanks with water spray.

Storage

Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place.

Further information on storage conditions

Keep away from heat.

Safety Data Sheet

according to Regulation (EU) No. 1907/2006

140.000 Renia - Ortec - Contactadhesive

Print date : 14.08.2007

Product code : 132

Page 3 of 7

8. Exposure controls/personal protection

Exposure limit values

Exposure limits (EH40)

CAS No.	Substance	ml/m ³	mg/m ³	F/ml	Category	Origin
110-82-7	Cyclohexane	100	350		TWA (8 h)	WEL
		300	1050		STEL (15 min)	WEL
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL

Exposure controls



Protective and hygiene measures

When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately after handling the product. Use protective skin cream before handling the product. Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feedingstuffs.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment. (gas filter type A2)

Hand protection

solvent-resistant gloves: nitrile rubber,
butyl-rubber, fluoroc rubber
Test suitability of gloves before use.

Eye protection

safety glasses

9. Physical and chemical properties

General information

Physical state : liquid
Colour : yellow
Odour : ester-like, mild

Important health, safety and environmental information

pH-Value :	not applicable	Test method
Changes in the physical state		
Melting point :	-4 - +8 °C	
Boiling point :	40-80 °C	DIN 53 171
Flash point :	-16 °C	DIN 51 755
Lower explosion limits :	0,6 vol. %	
Upper explosion limits :	13 vol. %	
Vapour pressure :	120 hPa	DIN 51 754
(at 20 °C)		
Density (at 20 °C) :	0.795 g/cm ³	DIN 51 757
Water solubility :	insoluble	

Safety Data Sheet

according to Regulation (EU) No. 1907/2006

140.000 Renia - Ortec - Contactadhesive

Print date : 14.08.2007

Product code : 132

Page 4 of 7

Viscosity / dynamic :
(at 20 °C)

1050 mPa·s DIN 53 015

Solvent content

79 %

Other information

Ignition temperature :

260 °C DIN 51 794

10. Stability and reactivity

Conditions to avoid

Above 130 °C, hazardous fumes may be released. No decomposition if used as directed.

Materials to avoid

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Hazardous decomposition products

Heating can release hazardous gases. Carbon oxides In the event of fire the following can be released: carbon dioxide (CO₂) Carbon monoxide

11. Toxicological information

Acute toxicity

Health injuries are not known or expected under normal use.

Specific effects in experiment on an animal

no data available No data is available on the product itself.

Corrosive and irritant effects

Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons. May cause skin and eye irritation in susceptible persons.

Severe effects after repeated or prolonged exposure

Inhalation of vapours in high concentration can cause narcotic effects and metabolic acidosis.

Carcinogenic/mutagenic/toxic effects for reproduction

No data is available on the product itself.

12. Ecological information

Ecotoxicity

The product is insoluble and floats on water.

Mobility

No data is available on the product itself.

Persistence and degradability

Taking into consideration the properties of several components, the product is estimated not to be readily biodegradable according to OECD classification.

Bioaccumulative potential

No data is available on the product itself.

Further information

Do not let product enter drains.

13. Disposal considerations

Advice on disposal

Dispose of as special waste in compliance with local and national regulations

Safety Data Sheet

according to Regulation (EU) No. 1907/2006

140.000 Renia - Ortec - Contactadhesive

Print date : 14.08.2007

Product code : 132

Page 5 of 7

Waste disposal number of waste from residues/unused products

080406 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

Waste disposal number of used product

080406 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

Contaminated packaging

Offer rinsed packaging material to local recycling facilities. Recycling of packaging materials (dual system).

14. Transport information

Land transport (ADR/RID)

UN number : 1133
ADR/RID class : 3
Classification code : F1
Warning plate
Hazard-no. : 33
Hazard label : 3
ADR/RID packing group : III
Limited quantity : LQ7, 5 Liter

Description of the goods

KLEBSTOFFE, mit entzündbarem flüssigem Stoff (mit einem Flammpunkt unter 23 °C und viskos gemäß 2.2.3.1.4) (Dampfdruck bei 50 °C höchstens 110 kPa)

Remarks (land transport)

Special Provision 640H
Tunnelbeschränkungscode 3 (E)

Inland waterways transport

UN number : 1133
ADNR class : 3
Classification code : F1
Hazard label : 3
Packing group : III
Limited quantity : 5 Liter

Description of the goods

adhesives

Marine transport

UN number : 1133
IMDG code : 3
Marine pollutant : --
Hazard label : 3
IMDG packing group : III
EmS : F-E,S-D
Limited quantity : 5 Liter

Description of the goods

adhesives

Remarks (marine transport)

Staukategorie A

Air transport

Safety Data Sheet

according to Regulation (EU) No. 1907/2006

140.000 Renia - Ortec - Contactadhesive

Print date : 14.08.2007

Product code : 132

Page 6 of 7

UN/ID number : 1133
ICAO/IATA-DGR : 3
Hazard label : 3
ICAO packing group : III

Description of the goods
adhesives

15. Regulatory information

Labelling

Danger symbols :

F - Highly flammable; Xi - Irritant; N - Dangerous for the environment



F - Highly flammable

Xi - Irritant

N - Dangerous for the environment

R phrases

11 Highly flammable.
67 Vapours may cause drowsiness and dizziness.
36/38 Irritating to eyes and skin.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S phrases

02 Keep out of the reach of children.
09 Keep container in a well-ventilated place.
16 Keep away from sources of ignition - No smoking.
23 Do not breathe gas .
25 Avoid contact with eyes.
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
37 Wear suitable gloves.
46 If swallowed, seek medical advice immediately and show this container or label.
61 Avoid release to the environment. Refer to special instructions / Safety data sheets.
29/56 Do not empty into drains, dispose of this material and its container to hazardous or special waste collection point.

Additional advice on labelling

According to (National equivalent of EC-Dir. 67/548), as amended, the product is labelled as follows:
The product is classified and labelled in accordance with Directive 1999/45/EC.

EU regulatory information

1999/13/EC (VOC) : 76,8 % (610,56 g/l)

National regulatory information

Water contaminating class : 2 - water contaminating

16. Other information

Full text of R-phrases referred to under sections 2 and 3

11 Highly flammable.
36 Irritating to eyes.
38 Irritating to skin.
50 Very toxic to aquatic organisms.
51 Toxic to aquatic organisms.
53 May cause long-term adverse effects in the aquatic environment.
65 Harmful: may cause lung damage if swallowed.

Safety Data Sheet

according to Regulation (EU) No. 1907/2006

140.000 Renia - Ortec - Contactadhesive

Print date : 14.08.2007

Product code : 132

Page 7 of 7

- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.
- 36/38 Irritating to eyes and skin.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Other data

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.