

Safety Data Sheet

according to Regulation (EU) No. 1907/2006

170.000 Renia - Ortec - Contact Adhesive

Print date : 22.06.2008

Product code : 170

Page 1 of 7

1. Identification of the substance/preparation and of the company/undertaking

Identification of the substance or preparation

170.000 Renia - Ortec - Contact Adhesive

Use of the substance/preparation

adhesives

Company/undertaking identification

Company name : Renia - GmbH
Chemische Fabrik
Street : Ostmerheimer Straße 516
Place : D-51109 Köln
Post-office box : 910 659
D-51076 Köln
Telephone : +49-(0)221-630799-0
Contact person : Dr. Julian Grimme
e-mail : info@renia.com
Internet : www.renia.com
Inquiry office : F & E, Labor
Emergency telephone : +49-(0)221-63079924
Telefax : +49-(0)221-630799-50
Telephone : 17

2. Hazards identification

Classification

Indications of danger : Highly flammable, Irritant, Dangerous for the environment
R-phrases :
Highly flammable.
Irritating to eyes and skin.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Vapours may cause drowsiness and dizziness.

Explication of special hazards for human health and environment

In use, may form flammable/explosive vapour-air mixture.

3. Composition/information on ingredients

Chemical characterization (preparation)

polychloroprene adhesive with modified synthetic resins and stabilizers in a mixture of organic solvents

Hazardous components

EC-No.	CAS-No.	Chemical name	Quantity	Classification
205-500-4	141-78-6	ethyl acetate	25-35 %	F, Xi R11-36-66-67
270-690-8	68476-50-6	Hydrocarbons, C _{>=5} , C ₅₋₆ -rich, Low boiling point naphtha - unspecified	20-30 %	F, Xn, Xi, N R11-38-65-67-51-53
203-806-2	110-82-7	cyclohexane	20-30 %	F, Xn, Xi, N R11-65-38-67-50-53

Full text of each relevant R phrase can be found in heading 16.

4. First aid measures

After inhalation

Move to fresh air in case of accidental inhalation of vapours. Consult a physician. If symptoms persist, call a physician.

After contact with skin

Safety Data Sheet

according to Regulation (EU) No. 1907/2006

170.000 Renia - Ortec - Contact Adhesive

Print date : 22.06.2008

Product code : 170

Page 2 of 7

Take off all contaminated clothing immediately. Wash off with soap and water. Grease skin after contact.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult a physician.

After ingestion

Do not induce vomiting. Call a physician immediately.

Advice to doctor

In case of shortness of breath, give oxygen. Risk of product entering the lungs on vomiting after ingestion.

5. Fire-fighting measures

Suitable extinguishing media

carbon dioxide (CO₂) dry chemical foam water spray

Extinguishing media which must not be used for safety reasons

high volume water jet

Special exposure hazards arising from substance or preparation itself, combustion products, resulting gases

In the event of fire and/or explosion do not breathe fumes. In case of fire production of HCl-gases.

Special protective equipment for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Additional information

Use water spray to cool unopened containers.

6. Accidental release measures

Personal precautions

Remove all sources of ignition. When using do not smoke. Ensure adequate ventilation.

Environmental precautions

Do not let product enter drains.

Methods for cleaning up/taking up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Dispose of as special waste in compliance with local and national regulations

7. Handling and storage

Handling

Advice on safe handling

Use only in well-ventilated areas. Use only in area provided with appropriate exhaust ventilation. Provide sufficient air exchange and/or exhaust in work rooms.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. In use, may form flammable/explosive vapour-air mixture.

Storage

Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place. Keep at temperatures between 5 and 40°C.

Advice on storage compatibility

Keep away from food, drink and animal feedingstuffs.

Safety Data Sheet

according to Regulation (EU) No. 1907/2006

170.000 Renia - Ortec - Contact Adhesive

Print date : 22.06.2008

Product code : 170

Page 3 of 7

Further information on storage conditions

Keep away from heat. Protect against freezing. Keep container tightly closed in a dry and well-ventilated place. Keep away from direct sunlight.

Storageclass (VCI) : 3

8. Exposure controls/personal protection

Exposure limit values

Exposure limits (EH40)

CAS-No.	Chemical name	ml/m ³	mg/m ³	F/ml	Category	Origin
110-82-7	Cyclohexane	100	350		TWA (8 h)	WEL
		300	1050		STEL (15 min)	WEL
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL
68476-50-6	Hydrocarbons, C ₅ =5, C ₅ -6-rich, Low boiling point naphtha - unspecified	200	1000		TWA (8 h)	MAK
					STEL (15 min)	MAK

Exposure controls



Protective and hygiene measures

When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately after handling the product. Use protective skin cream before handling the product. Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feedingstuffs.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment. (gas filter type A2)

Hand protection

solvent-resistant gloves: nitrile rubber, butyl-rubber, fluoroc rubber
Test suitability of gloves before use.

Eye protection

safety glasses

9. Physical and chemical properties

General information

Physical state : liquid
Colour : yellow
Odour : ester-like, mild

Important health, safety and environmental information

pH-Value :

Test method
not applicable

Changes in the physical state

Melting point :
Boiling point :

-4 - +8 °C
40 - 80 °C DIN 53 171

Safety Data Sheet

according to Regulation (EU) No. 1907/2006

170.000 Renia - Ortec - Contact Adhesive

Print date : 22.06.2008

Product code : 170

Page 4 of 7

Flash point :	-18 °C	DIN 51 755
Lower explosion limits :	0,6 vol. %	
Upper explosion limits :	13 vol. %	
Vapour pressure : (at 20 °C)	120 hPa	DIN EN 12
Density (at 20 °C) :	0.795 g/cm ³	DIN 51 757
Water solubility :	insoluble	
Viscosity / dynamic : (at 20 °C)	1050 mPa·s	DIN 53018

Solvent content

78 %

Other information

Ignition temperature : 260 °C DIN 51 794

10. Stability and reactivity

Conditions to avoid

Above 130 °C, hazardous fumes may be released. No decomposition if used as directed.

Materials to avoid

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Hazardous decomposition products

Heating can release hazardous gases. Carbon oxides In the event of fire the following can be released: carbon dioxide (CO₂) Carbon monoxide

11. Toxicological information

Acute toxicity

Health injuries are not known or expected under normal use.

Specific effects in experiment on an animal

no data available No data is available on the product itself.

Corrosive and irritant effects

Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons. May cause skin and eye irritation in susceptible persons.

Sensitising effects

contains Kolophonium

Severe effects after repeated or prolonged exposure

Inhalation of vapours in high concentration can cause narcotic effects and metabolic acidosis.

Carcinogenic/mutagenic/toxic effects for reproduction

No data is available on the product itself.

12. Ecological information

Ecotoxicity

The product is insoluble and floats on water.

Mobility

No data is available on the product itself.

Persistence and degradability

Taking into consideration the properties of several components, the product is estimated not to be readily biodegradable according to OECD classification.

Safety Data Sheet

according to Regulation (EU) No. 1907/2006

170.000 Renia - Ortec - Contact Adhesive

Print date : 22.06.2008

Product code : 170

Page 5 of 7

Bioaccumulative potential

No data is available on the product itself.

Further information

Do not let product enter drains.

13. Disposal considerations

Advice on disposal

Dispose of as special waste in compliance with local and national regulations

Waste disposal number of waste from residues/unused products

080406 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products)

Waste disposal number of used product

080406 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products)

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Offer rinsed packaging material to local recycling facilities. Recycling of packaging materials (dual system).

14. Transport information

Land transport (ADR/RID)

UN number : 1133
ADR/RID class : 3
Classification code : F1
Warning plate
Hazard-no. : 33
Hazard label : 3
ADR/RID packing group : III
Limited quantity : LQ7

Description of the goods

ADHESIVES containing flammable liquid
Auslöser:cyclohexane

Other applicable information (land transport)

Tunnelbeschränkungscode 3 (E)
: 640H
: 3
Auslöser: cyclohexane
: E

Inland waterways transport

UN number : 1133
ADNR class : 3
Classification code : F1
Hazard label : 3
Packing group : III
Limited quantity : LQ7

Safety Data Sheet

according to Regulation (EU) No. 1907/2006

170.000 Renia - Ortec - Contact Adhesive

Print date : 22.06.2008

Product code : 170

Page 6 of 7

Description of the goods

ADHESIVES containing flammable liquid
Auslöser: cyclohexane

Other applicable information (inland waterways transport)

: 640H

Marine transport

UN number : 1133
IMDG code : 3
Marine pollutant : •
Hazard label : 3
IMDG packing group : III
EmS : F-E, S-D
Limited quantity : 5 L

Description of the goods

ADHESIVES containing flammable liquid
Dangerous Component: cyclohexane

Other applicable information (marine transport)

Staukategorie A
: 223, 944, 955

Air transport

UN/ID number : 1133
ICAO/IATA-DGR : 3
Hazard label : 3
ICAO packing group : III
Limited quantity Passenger : 10 L
IATA-packing instructions - Passenger : 309
IATA-max. quantity - Passenger : 60 L
IATA-packing instructions - Cargo : 310
IATA-max. quantity - Cargo : 220 L

Description of the goods

ADHESIVES containing flammable liquid
Dangerous Component: cyclohexane

Other applicable information (air transport)

: Y309

15. Regulatory information

Labelling

Danger symbols :

F - Highly flammable; Xi - Irritant; N - Dangerous for the environment



F - Highly flammable



Xi - Irritant



N - Dangerous for the environment

R phrases

11 Highly flammable.
36/38 Irritating to eyes and skin.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
67 Vapours may cause drowsiness and dizziness.

Safety Data Sheet

according to Regulation (EU) No. 1907/2006

170.000 Renia - Ortec - Contact Adhesive

Print date : 22.06.2008

Product code : 170

Page 7 of 7

S phrases

- 09 Keep container in a well-ventilated place.
- 16 Keep away from sources of ignition - No smoking.
- 23 Do not breathe vapour .
- 29 Do not empty into drains.
- 33 Take precautionary measures against static discharges.

Additional advice on labelling

According to (National equivalent of EC-Dir. 67/548), as amended, the product is labelled as follows:
The product is classified and labelled in accordance with Directive 1999/45/EC.

EU regulatory information

1999/13/EC (VOC) : 78 % (620,1 g/l)

National regulatory information

Water contaminating class (D) : 2 - water contaminating

16. Other information

Full text of R-phrases referred to under sections 2 and 3

- 11 Highly flammable.
- 36 Irritating to eyes.
- 36/38 Irritating to eyes and skin.
- 38 Irritating to skin.
- 50 Very toxic to aquatic organisms.
- 51 Toxic to aquatic organisms.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 53 May cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)